

# Inner Core – OnePatch

Our OnePatch is a rig ready solution to isolate various casing integrity issues. Its compact design and simple operation enable repairs to be made efficiently, significantly reducing operational expenditure.

The tool can seal perforations or repair leaking casing while providing a large production conduit to bring the well back online. The device can be snubbed on a live well so there is no requirement to cease production before deployment.

With its robust construction, it is designed to last the life of the well.

## FEATURES

- Bottom-up hydraulic expansion system
- Premium elastomer seal at the top and bottom
- Shoe design enables simple drill out post expansion

## BENEFITS


- No personnel required for deployment
- Straddle intervals up to 25ft
- Makes directly up to the workstring
- NACE H<sub>2</sub>S compliant
- Air freight compatible design available
- Deployable on jointed, stick pipe or coiled tubing
- Quickly/immediatly deployable (i.e. these can be on the rig ready for urgent deployment)

## APPLICATIONS

- Isolation of tubular leaks
- Isolation of failed completion components
- Perforation shut off - Isolation of unwanted water & gas
- Isolation sand screen to negate sand ingress
- Perforation shut off – isolation post cement squeeze
- Corrosion isolation

## CORE PRODUCT SYNERGIES (CPS)

- Origin WBCU Portfolio
- CX-DB (Drillable Brush)



## SPECIFICATIONS

Parent Wellbore or Casing							Pre-Expanded Running Specs			Expanded Geometry				Expanded Performance	
OD	Weight	Wall Thickness	ID	API ID Min	API ID Max	Nominal Drift ID	OD	Wall Thickness	Maximum RIH OD	OD	Nominal ID	Special Drift	Expansion Ratio	Internal Yield Pressure	Collapse Pressure
[in]	[lb/ft]	[in]	[in]	[in]	[in]	[in]	[in]	[in]	[in]	[in]	[in]	[in]	[%]	[psi]	[psi]
7.000	29.0	0.408	6.149	6.293	6.184	6.059	5.500	0.304	6.029	5.978	5.413	5.353	10.7	6,861	3,770
7.000	26.0	0.362	6.241	6.380	6.276	6.151	5.500	0.304	6.121	6.074	5.518	5.458	12.8	6,777	3,500
7.000	23.0	0.317	4.643	4.765	6.366	6.241	5.500	0.304	6.211	6.168	5.620	5.560	14.9	6,695	3,250
7.000	20.0	0.272	6.421	6.551	6.456	6.331	5.500	0.304	6.301	6.262	5.722	5.662	17.0	6,610	3,010
5.500	23.0	0.415	4.643	4.765	4.670	4.545	4.250	0.250	4.545	4.538	4.066	4.006	8.4	8,090	5,080
5.500	20.0	0.361	4.751	4.868	4.778	4.653	4.250	0.250	4.655	4.651	4.190	4.130	11.7	7,944	4,560
5.500	17.0	0.304	4.865	4.976	4.892	4.767	4.250	0.250	4.767	4.770	4.321	4.261	15.2	7,786	4,040
5.500	15.5	0.275	4.923	5.031	4.950	4.825	4.250	0.250	4.825	4.830	4.387	4.327	17.0	7,704	3,780
4.500	15.1	0.337	3.804	3.904	3.826	3.701	3.500	0.254	3.701	3.716	3.235	3.175	8.1	10,032	7,770
4.500	13.5	0.290	3.898	3.993	3.920	3.795	3.500	0.254	3.795	3.814	3.346	3.286	11.8	9,844	7,070
4.500	12.6	0.271	3.936	4.029	3.958	3.833	3.500	0.254	3.833	3.832	3.366	3.306	12.5	9,809	6,940
4.500	11.6	0.250	3.978	4.069	4.000	3.875	3.500	0.254	3.875	3.876	3.416	3.356	14.2	9,721	6,640
4.500	10.5	0.224	4.030	4.118	4.052	3.927	3.500	0.254	3.927	3.931	3.478	3.418	16.3	9,610	6,270
4.500	9.5	0.205	4.068	4.154	4.090	3.965	3.500	0.254	3.965	3.972	3.524	3.464	17.8	9,528	6,010

1. All values for 7in. parent casing are based on MTX-60 material grade, 5.5in. and 4.5in. are based on MTX-70 material grade. Other material grades are available on request.

2. All values calculated at ambient temperature unless otherwise noted.

3. Coretrax makes no warranties, guarantees, or representations, express or implied, as to the accuracy of the data, calculations and or values contained herein. In no event shall Coretrax be liable for incidental, indirect, punitive, or consequential damages arising out of the use of any products, materials, data, calculations and or values herein. Values subject to change without notice. Hard copies are considered uncontrolled.